

Every opcode the 1.130 game client and the OpenDAoC server know, by feature family

34
missing in OpenDAoC

Server → client 136 opcodes

Families

- Session & login
- Character select & create
- World entry & regions
- Movement & position
- Objects, NPCs & targeting
- Combat, death & pets
- Spells, skills & effects
- Character progression
- Inventory & items
- Trade, merchants & market
- Chat, commands & UI
- Groups, LFG, guilds & friends
- Quests & tasks
- Crafting
- Housing
- Keeps, RvR & siege
- Relics
- Unclassified

- 6A Both sides implement it
- E5 Client knows it, OpenDAO doesn't
- E5 Dashed: family is inferred
- 5E Obsolete for 1.130
- A9P Seen in a retail session
- A9P Can travel over UDP

Row = high nibble, column = low nibble. Below, every opcode by family, with its OpenDAoC name, what it does and its sub-types.

How we know

The client side is daoc-re's map of the official 1130 client: every case of its receive dispatcher, and every call to its TCP and UDP send functions. The server side comes from OpenDaoC's source: its handler registrations and send methods. Live sessions on OpenDaoC and the official servers confirm or correct the guesses.

An opcode is not a message

Many opcodes carry a sub-type that selects a different message: chat types, update kinds, character-create operations. Character delete, for one, is operation 3 inside character create. The chips list those sub-types.

Guesses are marked

Opcodes without an OpenDAOc name carry a best guess, from daoc-re's clues about where the client uses them; dashed cells and *guess* tags mark them. 65 opcodes were seen in a decoded official-server session. Corrections welcome.

eveofdarkness.org
2026-10-28 · layout and text CC BY 4.0
and sub-types from OpenDAoC (GPL-3.0)